

LE MAT (THE MATT)

Information and Technical Support:
export@vermillon-deco.com

PRODUCT DESCRIPTION

Ultra matt paint in aqueous phase based on acrylic dispersion for walls, ceilings and living rooms.

- Interior/Exterior
- Ultra matt
- Easy to use
- Practically odour-free
- Water resistant
- Breathing
- No yellowing

APPLICATION AREAS

- Plaster and plaster-based products / Plasterboards
- Concrete, cement, wooden panels
- Cement coating / Bricks
- Wallpaper
- Old paint

Our advice: Select an adapted primer by Mercadier depending on a preferred finish colour:

- Grey: FARSI, MALOSSOL, MAZARIN, OPIUM, PRINCE, RIGOLETTO, VELVET
- Yellow: ALICE, NACHOS, ROMANESCO, STAR FRUIT, TOFFEE, TATIN, BERTHE, RIO DULCE
- Rose: BRAVO!, CALYPSO, COCORICO, GERONIMO, KARMA, KIR, PITAYA, TANGERINE, TSAR, BOURKE
- White: OTHER COLOURS

SURFACE PREPARATION

Do not neglect surface preparation. This is an essential part in painting process which insures the longevity of the finishing coating. Remove all the specs of dirt and scale from the area concerned with the help of an adapted cleaning agent. Rinse and leave to dry. Remove all the grease and oil traces with a water-based grease-remover. Rinse the whole area. Remove as much as possible the grease traces, nicotine and moisture with a water solution of grease-remover. The surface must be prepared according to the general practices of a Building Code: sound, dry, cohesive and clean for application.

Plaster and plaster-based products

Leave the plaster to dry for at least 30 days. Place a layer of IMPRESSION (The Wall&Ceiling Primer).

Concrete, cement, brick

Remove all rough bits, specs of dirt and dust before placing the paint. We advise to place the first layer of IMPRESSION (The Wall&Ceiling Primer).

Old paint

Clean the whole area with water and soap. Rinse well and leave to dry. Place a layer of IMPRESSION (The Wall&Ceiling Primer) if necessary.

Wooden panels

All the wood must be correctly cleaned. Fill in all the cracks and holes with paste wood filler, then polish well. To avoid wood sweating it is advised to place fix the surface with a layer of ACCROCHE (The Bonding Undercoat).

Aluminium and galvanised steel

Remove all the grease, oil traces and other specs of dirt with a water-based grease-remover. It is necessary to remove corrosion with the help of sand paper, glass wool or another abrasive. Then, place a layer of ACCROCHE (The Bonding Undercoat).

Other surfaces: Please, contact us.

APPLICATION

Before placing the paint study and follow the recommendations on surface preparation. Two layers of "LE MAT" are sufficient for already painted surface after preparation. For non-painted supports (especially porous ones), it is advised to place a layer of a primer (IMPRESSION or ACCROCHE) suitable for your surface and then two layers of "LE MAT". The paint is applied with a brush, roller or a sprayer gun. Normally it is not necessary to dilute the paint (10% maximum is tolerated). Do not apply the paint under direct sunlight. The temperature at application must be between 6 °C and 34 °C.

Theoretical coverage: 7 to 14 m²/l

Drying time: Away from dust: 30 min - 1 hour

Recoverable: 4 hours

Setting: 2-3 days

With an Airless:

Pressure Airless: 150 - 180 bar

Nozzle : 0,021" - 0,027"

Angle : 50°

No dilution is required.

Our advice:

- The covering power varies depending on a primer used, nature of the surface and on the colour.
- Certain high pigmented colours might need the 3rd layer for a perfect render.
- To avoid leaving the traces of tools, apply the paint crossing your movements, starting with the dry zone and finishing with the just painted one.

CLEANING

Immediately after use wash your hands and clean the tools with water and soap.

CHARACTERISTICS

Basic data for white paint at 20°C

Density: 1.4 g/cm³

Weight solids: +/- 61 % of mass

Volume solids: +/- 42 % of volume

Recommended thickness of dry film: 75 micrometres

Recommended thickness of wet film: 150 micrometres

Flashpoint: /

Storage: To be stored in an original packaging in a cool place for 12 months maximum.

APPLICATION CONDITIONS

Temperatures: > 3°C, < 50 °C (air, surface, equipment and materials)

Relative moisture of the surface: 85% maximum

HYGIENE AND SAFETY

Keep out of children's reach.

Volatile Organic Compound (VOC):

VOC amount in this paint is very low.

Exposure limit value according to the norm n°2010/79/UE: Class A: 30 g/L

This product contains max 30 g/L.



- VOC Emissions:

In accordance with the new French regulations that establish limit value for the VOC (Volatile Organic Compound) present in construction materials, this product MERCADIER respects the environment. This regulation states that construction and decoration products must be provided with a label indicating the level of volatile organic compound emission in a simple and readable way. We have the pleasure to confirm that this product is A+ (the lowest possible VOC emission value).

Safety data sheet: please, contact us.

The information contained in this document is indicative and must be completed with an appropriate description of nature and state of the surface.