

METALLIC REPAIR SEALER

Information and Technical Support: export@mercadier-group.com

PRODUCT DESCRIPTION

- Metallic sealer to maintain and renovate decorative concrete already varnished.
- White non-toxic ready-to-use liquid.
- Color-free with satin appearance when dried.
- Slows down varnish wear creating a strong and resistant film on the surface.
- Brightens up colors and restores the original glow of your varnish.
- Anti-slip qualities.
- Facilitates maintenance and cleaning.

APPLICATION AREAS/SURFACES

- Indoors
- Floors

NECESSARY TOOLS

- Flat sponge mop or floorcloth.
- The tools must be cleaned with water immediately after use.

SURFACE PREPARATION

- Carry out wet cleaning.
- Let the surface dry.

MIX PREPARATION

- Ready to use. Do not dilute.
- Shake well the cans before application.

APPLICATION

- Little by little as you move forwards pour the product onto the surface.
- Put and spread the Metallic Repair Sealer on your surface in a uniform manner using a flat sponge mop. Do not leave any puddles.
- Leave to dry.

FINAL DRYING/BACK INTO SERVICE

- Dry to touch: for about 30 min.
- Waiting time indicated is provisory; it varies depending on weather conditions.

REGULAR MAINTENANCE/RENOVATION

- Use shampoo for regular maintenance after application of Metallic Repair Sealer.
- In order to preserve the product and its sealer (varnish, wax etc) we advice to place the felt pads under the legs of the furniture, chairs etc., even if they are in plastic.
- Do not leave any colored water spots or grease stains. Wipe them out as soon as possible.
- To clean the surface use non-aggressive cleaning agents.

- It is strictly forbidden to use ammonia-containing cleaning agents as well as anti-scale concentrated cleaners.
- It is important to maintain the surface regularly placing a new layer of the last sealing product (for this you might need to clean and slightly polish the surface to restore a good grip).
- Frequency of this operation is varied depending on the way the area is used (test with a water drop: see if the drop is absorbed into the surface).

COVERAGE/PACKAGING/STORAGE

- Coverage: 15 to 20 m² per liter.

RECOMMENDATION AND WARNING

- See the most recent version of this technical specification (see website). Our distributors or technical support are at your disposal for any clarification.
- Performance and durability guarantees for the decorative coating may be given only in case a complete system of MERCADIER products is used (primer, product itself, sealer) and strictly according to instructions for application and maintenance of the system. Thus, the manufacturer will not be liable for poor product's performance if an application did not conform to our instructions and if the integral system was not used.
- All the information, tips and advice relative to final illustration of MERCADIER products are given in good faith. They are based on knowledge and experience that MERCADIER has acquired so far regarding its products that were appropriately stored and handled, and applied in normal conditions. In practice, the differences between materials, surfaces and specific application conditions are such that provided information, written recommendations or given advice do not imply any warranty of merchantability other than the legal warranty against hidden defects.